

# FLATLIGHT FL1 30 m IP41



## FLATLIGHT FL1

What began as a feasibility study ended as the Flatlight FL1. With a 3 mm thick frame, homogeneous lighting, the enclosure is thinner than most smartphones. Particularly suitable in representative surroundings.



FLATLIGHT FL1 SYSTEM LUMINAIRE RECHARGEABLE BATTERY LUMINAIRE

Viewing distance	30 m	
Degree of protection	IP41	
Class	I	
Enclosure material	Aluminium	
Enclosure colour/surface	Silver anodised	
Terminal block	3 x 2.5 <sup>□</sup> for through wiring	
Light source	LED	
Ambient temperature	-20° C to +40° C	0° C to +40° C
Connected load (AC/DC)	6.1 VA/3.5 W	
Supply voltage	230V ± 10 %, 50/60 Hz / 176-275 V DC	230V ± 10 %, 50/60 Hz
Rechargeable battery	4.8 V/0.8 Ah (NiMH)	

VERSIONS

1 h with auto-check   with BUS check		•
3 h with auto-check   with BUS check		•
8 h with auto-check   with BUS check		
without monitoring module	•	
with monitoring module	•	
with DALI monitoring		
Cinema version		

SPECIAL FEATURE

- Unobtrusive all-round frame (3 mm)

FL1W WALL MOUNTED

